



Shell Helix *HX8 Synthetic 5W-40*

Fully synthetic motor oil - Relentless performance, cleansing and protection

Shell Helix HX8 Synthetic works hard to help keep modern engines clean and protected. It helps to prevent the formation of harmful deposits that can lead to performance loss. Its excellent deposit protection is suitable for all OEM-recommended drain intervals.

Proud Drivers Choose Shell Helix

Performance, Features & Benefits

- **Superior active cleansing technology**¹
Actively locks away harmful performance-robbing deposits.
- **Active clean-up**
Helps to remove sludge left behind by inferior oils²
- **Excellent wear protection**³
Helps to extend engine life by protecting against wear, even in the toughest driving conditions.
- **Long-term resistance to oil degradation**
Helps to maintain protection throughout the oil-drain interval.
- **Long life**
Suitable for all equipment-manufacturer-recommended oil-drain intervals.
- **Enhanced low-temperature performance**
Faster oil flow for quicker engine warm-up⁴
- **Low-evaporation formulation**⁵
Low oil consumption for less frequent top-up.
- **Multi-fuel capability**
Can be used for gasoline, diesel and gas engines, and is also suitable for biodiesel and gasoline/ethanol blends.

¹ Compared with Shell Helix mineral oils

² Based on a severe sludge clean-up test

³ Based on Sequence IVA engine test carried out at an independent laboratory

⁴ Compared with higher-viscosity oils

⁵ Based on NOACK volatility test and equipment manufacturers' requirements

Main Applications

- Shell Helix HX8 Synthetic's formulation can be used in engines in a wide variety of modern vehicles that face these demanding driving conditions, and should be recommended for customers who want to keep the same oil-drain interval and are carrying heavy loads, operating in extreme climates or driving in congested stop-start city traffic.
- Shell Helix HX8 Synthetic can be used for gasoline engines, diesel engines (without particulate filters) and gas engines, and it is also suitable for use with biodiesel and gasoline/ethanol blends.

Specifications, Approvals & Recommendations

- API SN/CF
- ACEA A3/B3, A3/B4
- VW 502.00/505.00
- MB-Approval 229.3
- Renault RN0700, 0710
- Meets the requirements of Fiat 9.55535-N2 and 9.55535-M2
- To find the right Shell Helix product for your vehicles and equipment, please consult Shell LubeMatch at: <http://lubematch.shell.com>
- Advice on applications not covered here may be obtained from your Shell or Shell Lubricants distributor representatives or technical help desks.

Typical Physical Characteristics

Properties			Method	Shell Helix HX8 Synthetic 5W-40
Kinematic Viscosity	@100°C	cSt	ASTM D445	14.45
Kinematic Viscosity	@40°C	cSt	ASTM D445	87.42
Viscosity Index			ASTM D2270	172
MRV	@-35°C	cP	ASTM D4684	20200
Density	@15°C	Kg/m ³	ASTM D4052	843.3
Flash Point		°C	ASTM D92	242
Pour Point		°C	ASTM D97	-45

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

• Health and Safety

Shell Helix HX8 Synthetic 5W-40 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from your Shell representative.

• Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.